

DECLARATION OF PERFORMANCE

No. PTS - MARMOFINISH FW FINAL

1. Unique identification code of the product-type: MARMOFINISH FW FINAL

2. Intended use/es: Concrete repair product for non-structural repair (R1-PCC), for uses with low performance requirements in buildings and civil engineering works not subject to reaction to fire regulations.

3. Manufacturer: EAGLE S.A. / AETOS A.E.

INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY

BRANCH: BUILDING PRODUCTS PRODUCTION PLANT "MARMODOM" INDUSTRIAL PARK OF PROSOTSANI, GR 66200 DRAMA, GREECE.

4. System/s of AVCP: System 4

5. Harmonised standard: EN 1504-3:2005

Notified body/ies: No tasks for the notified body

6. Declared performance/s:

Essential characteristics	Performance	Harmonised Technical Specification
Compressive strength:	Class R1	
Chloride ion content:	≤ 0.05%	
Adhesive Bond:	≥ 1.5 MPa	
Capillary absorption:	≤ 0.5 kg*m ⁻² *h ^{-0,5}	EN 1504-3:2005
Reaction to fire	NPD	
Dangerous substances	See SDS	





The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by:

Athanasios Lazaridis Q.C. / R&D Manager

At: Prosotsani, Drama, Greece

on 12/05/23

REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the safety data.







16

EAGLE S.A. / AETOS A.E.

INDUSTRIAL, COMMERCIAL & TRANSPORT COMPANY
BRANCH: BUILDING PRODUCTS PRODUCTION PLANT "MARMODOM"
Industrial park of Prosotsani, 66200 Drama, Greece

DoP No. PTS - MARMOFINISH FW FINAL

EN 1504-3

MARMOFINISH FW FINAL

Concrete repair product for non-structural repair (R1-PCC), for uses with low performance requirements in buildings and civil engineering works not subject to reaction to fire regulations.

Compressive strength: Class R1

Chloride ion content: $\leq 0.05\%$

Adhesive Bond: ≥ 1.5 MPa

Capillary absorption: $\leq 0.5 \text{ kg} \cdot \text{m}^{-2} \cdot \text{h}^{-0.5}$

Reaction to fire: NPD

Dangerous substances see SDS

